


Construction Timber in Spruce

finger jointed timber, 4-sides planned

planned and charging cross section			quality	package unit
width [mm]	hight [mm]	length	B	140 pc./pac.
45	75	4,00 m		1,89 m ³ /Pkt
45	75	5,00 m		2,36 m ³ /Pkt
45	75	6,00 m		2,84 m ³ /Pkt

Spruce



finger jointed timber



finger jointed timber




glulam

Konstruktionsleimbinder 4-seitig gehobelt

planned and charging cross section			quality	package unit
width [mm]	hight [mm]	length	B	100 pc./pac.
105	105	1,70 m		1,87 m ³ /pac.
105	105	1,80 m		1,98 m ³ /pac.
105	105	1,90 m		2,09 m ³ /pac.
105	105	2,00 m		2,21 m ³ /pac.
105	105	2,10 m		2,32 m ³ /pac.
105	105	2,30 m		2,54 m ³ /pac.
105	105	2,77 m		3,05 m ³ /pac.
105	105	2,99 m		3,30 m ³ /pac.
100	100	4,00 m		4,00 m ³ /pac.
100	100	5,00 m		5,00 m ³ /pac.

Spruce



glulam

other dimensions and cross sections on request

KD about 14 %

Bonding with EPI-adhesive

surface: 4-sides planed, chamfered edges

thickness of lamellas: standard 25 mm (partially also thinner lamellas are used)

no strength class